Square Boxes and Accessories

4" Square Old-Work Box with Swing Ears

CAT. NO.	DESCRIPTION	STD. CTN.
52171-OW	Metallic 4"-Sq. x 2⅛"D Old-Work Box with factory-mounted swing ears	25
OW SWING EAR	Swing Ears only (for field installation) with self-threading screws	50 (25 pair)

4" Square Boxes

CAT. NO.	DEPTH (IN.)	CU. IN. CAPACITY	CLAMPS	BRKTS.	KNOCKOUTS (IN.) EA. SIDE CONDUIT	EA. END CONDUIT	BOTTOM CONDUIT	STD. CTN.
With Non-Metallic Sheathed Cable Clamps								
52151 N	1½	21.0	C-5	—	2–½, 1–½, ¾E	2	1–½	50
52151 MS N*	1½	21.0	C-5	MS	2–½, 1–½, ¾E	2	1–½	25
52151 BN*	1½	21.0	C-5	B	2–½, 1–½, ¾E	2	1–½	25
52151 VN*	1½	21.0	C-5	SV	2–½, 1–½, ¾E	2	1–½	25
52151 CVN*	1½	21.0	C-5	CV	2–½, 1–½, ¾E	2	1–½	25
52151CVNP*	1½	21.0	C-5	CV	2–½, 1–½, ¾E	2	1–½	25
52171 N	2⅛	30.3	C-5	—	2–½, 1–½, ¾E	2	1–½	25
52171-VN*	2⅛	30.3	C-5	SV	2–½, 1–½, ¾E	2	1–½	25
With Conduit KOs								
52141-1/2	1¼	18.0	—	—	2–½	3–½	5–½	50
52151 1/2	1½	21.0	—	—	3–½	3–½	5–½	50
52151-3/4	1½	21.0	—	—	2–¾	2–¾	3–½, 2–¾	50
52151 1/2 3/4	1½	21.0	—	—	2–½, 1–¾	2–½, 1–¾	3–½, 2–¾	50
521511234P	1½	21.0	—	—	2–½, 1–¾	2–½, 1–¾	3–½, 2–¾	50
52151-3/4-W	1½	21.0	—	—	2–¾	2–¾	3–½, 2–¾	50
52151B1234*	1½	21.0	—	B	2–½, 1–½, ¾E	2–½, 1–¾, ¾E	3–½, 2–½, ¾E	25
52151-1/2 & 3/4-EW	1½	21.0	—	—	2–½, 1–½, ¾E	2–½, 1–½, ¾E	3–½, 2–½, ¾E	50
521511234EWGB (Ground bump)	1½	21.0	—	—	2–½, 1–½, ¾E	2–½, 1–½, ¾E	2–½, 2–½, ¾E	50
521511234EWGBP (Ground bump with 10½" ground wire)	1½	21.0	—	—	2–½, 1–½, ¾E	2–½, 1–½, ¾E	2–½, 2–½, ¾E	50

** All Bracketed boxes come complete with eccentric knockouts.*

Per UL 514A, suitable for use without a bonding jumper in circuits above or below 250 volts. Pigtail wire is #12 AWG insulated, 10½" long.




52171-OW




OW Swing Ears




52151 N




52151 MS N MS bracket for 1⅛", 2½", 3⅝", 4"*




52151 BN B bracket mounted flush*



52151 VN SV bracket mounted flush*



52151 CVN CV bracket mounted flush*



52151 CVNP



52171 N



52171-VN SV bracket mounted flush*



52141-1/2




52151 1/2



52151-3/4




52151 1/2 3/4



521511234P




52151-3/4-W




52151B1234 B Bracket mounted flush



52151-1/2 & 3/4-EW



521511234EWGB




521511234EWGBP

Square Boxes and Accessories


4" Square Boxes *(continued)*

CAT. NO.	DEPTH (IN.)	CU. IN. CAPACITY	CLAMPS	BRKTS.	KNOCKOUTS (IN.) EA. SIDE CONDUIT	EA. END CONDUIT	BOTTOM CONDUIT	STD. CTN.
With Conduit KOs (continued)								
521511234EWP*	1½	21.0	—	—	2–½, 1–½, ¾E	2–½, 1–½, ¾E	3–½, 2–½, ¾E	50
52151 MS 1/2 & 3/4*	1½	21.0	—	MS	2–½, 1–½, ¾E	2–½, 1–¾, ¾E	3–½, 2–½, ¾E	25
52151-V-1/2 & 3/4*	1½	21.0	—	SV	2–½, 1–½, ¾E	2–½, 1–¾, ¾E	3–½, 2–½, ¾E	25
52151 CV 3/4*	1½	21.0	—	CV	2–¾	2–3/4	3–½	25
52151 CV 1/2 3/4*	1½	21.0	—	CV	2–½, 1–½, ¾E	2–½, 1–¾, ¾E	3–½, 2–½, ¾E	25
52151DV12*	1½	21.0	—	DV	2–½, ¾E	3–½, ¾E	3–½, ¾E	25
521711234E	2⅛	30.3	—	—	2–½, 1–½, ¾E	2–½, 1–½, ¾E	3–½, 2–½, ¾E	50
521711234EP (With 10½" ground wire)	2⅛	30.3	—	—	2–½, 1–½, ¾E	2–½, 1–½, ¾E	2–½, 2–½, ¾E	50
52171 MS 1/2 3/4*	2⅛	30.3	—	MS	2–½, 1–½, ¾E	2–½, 1–½, ¾E	3–½, 2–½, ¾E	25
52171MSP* (With 10½" ground wire)	2⅛	30.3	—	MS	2–½, 1–½, ¾E	2–½, 1–½, ¾E	3–½, 2–½, ¾E	25
52171 3/4	2⅛	30.03	—	—	2–¾	2–¾	3–½, 2–¾	50
52171 1	2⅛	30.03	—	—	2–1	2–1	3–½, 2–¾	50
52171 V 1/2 & 3/4*	2⅛	30.03	—	SV	2–½, 1–½, ¾E	2–½, 1–½, ¾E	3–½, 2–½, ¾E	25
52171-CV-1/2 & 3/4*	2⅛	30.03	—	CV	2–½, 1–½, ¾E	2–½, 1–½, ¾E	3–½, 2–½, ¾E	25
52171-EW-SSX*	2⅛	30.03	—	SSX	—	—	—	—
521711234EP*	2⅛	30.03	—	v	2–½, 1–½, ¾E	2–½, 1–½, ¾E	3–½, 2–½, ¾E	25
52171-B-1/2 & 3/4	2⅛	30.03	—	—	2–½, 1–½, ¾E	2–½, 1–½, ¾E	3–½, 2–½, ¾E	25


** All bracketed boxes come complete with eccentric knockouts. Per UL514A, suitable for use without a bonding jumper in circuits above or below 250 volts. Pigtail wire is #12 AWG insulated, 10½" long.*




521511234EWP



52151 MS 1/2 & 3/4 For use on 1⅝", 2½", 3⅝", 4" studs




52151-V-1/2 & 3/4 SV Bracket mounted flush



52151 CV 3/4 CV Bracket mounted flush



52151 CV 1/2 3/4 CV Bracket mounted flush



52151DV1/2 DV Bracket provides offset




521711234E



521711234EP



52171 MS 1/2 3/4 MS bracket for 1⅝", 2½", 3⅝", 4", 6" metal studs*



52171MSP



52171 3/4




52171 1



52171 V 1/2 & 3/4 SV bracket mounted flush



52171-CV-1/2 & 3/4 CV bracket mounted flush



521711234EP

CAT. NO.	DESCRIPTION	EARS	BRACKETS	EACH SIDE KO	EACH END KO	BOTTOM KO	CU. IN. CAPACITY	STD. CTN.
521911234	3½"-deep 4"-square red box	—	—	4 x ½" & ¾" Combo	2 x ½" & ¾" Combo	4 x ½" & ¾" Combo	46	24
521911234CV	3½"-deep 4"-square red box w/side mounting bracket	—	CV	4 x ½" & ¾" Combo	2 x ½" & ¾" Combo	4 x ½" & ¾" Combo	46	10

Thomas&Betts

United States
Tel: 901.252.8000
800.816.7809
Fax: 901.252.1354

Technical Services
Tel: 888.862.3289

www.tnb.com


4" Square Boxes *(continued)*

CAT. NO.	DEPTH (IN.)	CU. IN. CAPACITY	CLAMPS	BRKTS.	KNOCKOUTS (IN.) EA. SIDE CONDUIT	EA. END CONDUIT	BOTTOM CONDUIT	STD. CTN.
With Armored Cable/Metal-Clad Clamps								
52151 X	1¼	21.0	C-3	—	2–½, 1–½, ¾E	2	1–½	50
52151XP	1¼	21.0	C-3	—	2–½, 1–½, ¾E	2	1–½	50
52151 BX*	1¼	21.0	C-3	B	2–½, 1–½, ¾E	2	1–½	25
52151 VX*	1¼	21.0	C-3	SV	2–½, 1–½, ¾E	2	1–½	25
52151 CVX*	1¼	21.0	C-3	CV	2–½, 1–½, ¾E	2	1–½	25
52151 MS X*	1¼	21.0	C-3	MS	2–½, 1–½, ¾E	2	1–½	25
For Armored Cable and Metal-Clad Cable Clamps								
52171 X*	2⅛	30.3	C-3	—	2–½, 1–½, ¾E	2	1–½	25
52171 MSX*	2⅛	30.3	C-3	MS	2–½, 1–½, ¾E	2	1–½	25
52171MSXP (With 10½" ground wire)	2⅛	30.3	C-3	MS	2–½, 1–½, ¾E	2	1–½	25
52171-CVX*	2⅛	30.3	C-3	CV-2	½ –¾	—	—	25


** All bracketed boxes come complete with eccentric knockouts. Per UL514A, suitable for use without a bonding jumper in circuits above or below 250 volts. Pigtail wire is #12 AWG insulated, 10½" long. All 52171 series boxes have a raised ground bump.*




52151 X




52151XP




52151 BX B bracket mounted flush*




52151 VX SV bracket mounted flush*




52151 CVX CV bracket mounted flush*




52151 MS X MS bracket for 1⅝", 2½", 3⅝", 4" metal studs*



52171 X



52171 MSX MS bracket for 1⅝", 2½", 3⅝", 4" metal studs*



*52171MSXP**

CAT. NO.	DESCRIPTION	CLAMPS	EACH SIDE CONDUIT	EACH END CONDUIT	BOTTOM CONDUIT	CU. IN. CAPACITY	STD. PACK.
52171-EW-SSX	2⅛"-deep with conduit KOs	—	1½", 1½" & ¾"E	2½", 1½" & ¾"E	2½", 2½" & ¾"E	30	20
52151-EF-SSX	1½"-deep with conduit KOs	—	1½", 1½" & ¾"E	2½", 1½" & ¾"E	2½", 2½" & ¾"E	21	20
52171-X-SSX	2⅛"-deep with armored cable clamps	C3	1½", 1½" & ¾"E	2 Cable	1½"	30	20
52151-X-SSX	1½"-deep with armored cable clamps	C3	1½", 1½" & ¾"E	2 Cable	1½"	21	20
CXLESSX	3½"-deep with armored cable clamps	C3	2½"	1½" & 2 Cable	1½"	15	20

Vapor Tite Boxes

- All K.O.'s pressed flush but still easy to remove
- No holes anywhere
- Top edge of boxes are flush at ears so gasket seals out all air

CAT. NO.	DESCRIPTION	DEPTH	STD. PKG.
52151-SVT	4" Sq. Box, ½" and ¾" K.O. Side and Bottom	1½"	50
52C1-VT	4" Sq. Blank Cover with Gasket	Flat	50
52171-SVT	4" Sq. Box, ½" and ¾" K.O. Side and Bottom	2⅛"	25
72C1-VT	4 11/16" Sq. Blank Cover with Gasket	Flat	50
72171-SVT	4 11/16" Sq. Box, ½" and ¾" K.O. Side and Bottom	2⅛"	25
54151-VT	4" Sq. Box, ½" K.O. Side and Bottom	1½"	50
54C1-VT	4" Oct. and Round Box Blank Cover	Flat	50